



# OP-305

## Meter reading optical probe OP-305 with RS-232 output signal


The Optical Probe OP-305 with RS-232 output is an interface that communicates with a peripheral device such as an electric meter, water meter, heat meter or gas meter via infrared. Any other device that supports the European standard IEC 62056-21 (IEC 1107) is compatible with this product.

The Optical Probe OP-305 with RS-232 port and a D-Sub 9 pin male connector is suitable if consumption data is supposed to be read out by a peripheral device such as a handheld device.

Specific adjustments is possible by order.


### Mechanical description of the optical probe OP-305

- Connector: a serial DB-9 male connector
- infrared filter against external light influences
- Dimensions (Ø x H): approx. 32 x 26 mm
- Magnetic holding force: > 15 N
- Casing material : ABS
- Cable: length 2 m, Ø 4,5 mm, four-wire cable(LAPP KABEL GERMANY)
- Weight: approx. 110 gr.



### Electronic description of the optical probe OP-305

- Standard: IEC 62056-21 (IEC 1107)
- Power supply: no power supply required. Supplied from RS-232 interface
- Consumed current: approx. 5 mA (Transmitting operation)
- Signal level: Compatible with EIA-232 (RS-232)
- Data baud rate : 19200 bit/S
- Wavelength: 880nm
- Echofilter: yes



Pin	Signal	Color	Description
2	RXD	□	RS-232 Receive Data
3	TXD	■	RS-232 Transmit Data
4	VCC	■	+5v or DTR
5	GND	■	Ground



**GERMAN METERING GmbH**

Reutenweg 65,  
60323 Frankfurt am Main, Germany  
Telephone: +49 (0)69 / 77062206, Fax: +49 (0)69 / 77062226  
www.german-metering.com

