



OP-340

Meter reading optical probe OP-340 with RS-232 output signal

The Optical Probe OP-340 with RS-232 output is an interface that communicates with a peripheral device such as an electric meter, water meter, heat meter or gas meter via infrared. Any other device that supports the European standard IEC 62056-21 (IEC 1107) is compatible with this product.

The Optical Probe OP-340 with RS-232 port and RJ-45 connector is suitable if consumption data is supposed to be read out by a peripheral device such as a handheld device.


Specific adjustments is possible by order.

Mechanical description of the optical probe OP-340

- Connector: RJ-45
- infrared filter against external light influences
- Dimensions (Ø x H): approx. 32 x 26 mm
- Magnetic holding force: > 15 N
- Casing material: ABS
- Cable: length 2m, Ø 4,5 mm, four-wire cable (LAPP KABEL GERMANY)
- Weight: approx. 95 gr.


Electronic description of the optical probe OP-340

- Standard: IEC 62056-21 (IEC 1107)
- Power supply: no power supply required. Supplied from RS-232 interface
- Consumed current: approx. 5 mA (Transmitting operation)
- Signal level: Compatible with EIA-232 (RS-232)
- Data baud rate: 19200 bit/S
- Wavelength: 880nm
- Echofilter: yes



GERMAN METERING GmbH

Reuterweg 65,
60323 Frankfurt am Main, Germany
Telephone: +49 (0)69 / 77062206, Fax: +49 (0)69 / 77062226
www.german-metering.com



Pin	Signal	Color	Description
3	TXD	Green	RS-232 Receive Data
4	RXD	White	RS-232 Transmit Data
5	GND	Black	Ground
6	VCC	Red	+5 Volt or DTR

